26OPzS-ET 4550 SOLAR

Vented Flooded Deep Cycle Battery

Performance characteristics

Nominal Voltage	2V
Number of cells	1
Design Life	20 years
Nominal Capacity 25°C (77°F)	
120 hour rate (39A, 1.85V)	4687Ah
48 hour rate (90A, 1.80V)	4320Ah
10 hour rate (368.2A, 1.8V)	3682Ah
Internal Resistance	
Fully Charged Battery 25°C (77°F)	0.11mOhm
Electrolyte	
Nominal S.G at 25°C = 1.240kg/l	
Operating Temperature Range	-20~55°C
Maximum Discharge Current 25°C (77°F)	3446A
Charge Methods: Constant Voltage Charge 25°C (77°F)	
Cycle use	2.40V (time limited)
Maximum charging current	1472A
Standby use	2.25V ± 1%
Temperature compensation	-3.5mV/°C/Cell
Terminal Torque	23Nm

Capacities C10-C240

Cell Type Ue (100%) / VPC Ref Temp	C10 1.80 25°C	C12 1.80 25°C	C20 1.80 25°C	C24 1.80 25°C	C48 1.80 25°C	C72 1.80 25°C	C100 1.85 25°C	C120 1.85 25°C	C240 1.85 25°C
26OPzS-ET 4550 SOLAR	3682	3723	4046	4147	4320	4530	4546	4687	4874

Cycles vs DOD of OPzS Solar Power



Features

- High energy density
- Robust tubular positive electrode design, compliant with DIN 40736
- Minimal maintenance due to low antimony alloy and large electrolyte volume
- Operating temperature -20°C to +55°C
- Low self discharge rate of approximately 3% per month at 20°C
- EUROBAT design life: Long Life >12 years
- Fully recyclable with low CO_2 footprint
- High cyclic performance
- 3000+ cycles @ 60% DOD @ IUI charging

Applications

- Solar/Wind Power Stations
- Traffic Systems
- Hydro Power Generation
- Off Grid Solutions
- Telecommunications/ Mobile Phone Stations
- Power Distribution Companies

Dimensions and weight

Length (max)	215 mm
Width (max)	580 mm
Height: H1 (max)	775 mm
Total height: H2 (max)	790 mm
Filled weight (max)	236.8 kg



Compliant with IEC 60896-11 / IEC 61427